

LANCOM LX-7200

Wi-Fi 7 for future-proof wireless networks



The Wi-Fi 7 Access Point LANCOM LX-7200 combines the highest levels of security, sustainability, and intelligent automation for modern WLAN environments with medium user density. By exclusively using the 6 GHz frequency band, which is reserved exclusively for WLAN, it ensures a smooth operation with low latency and maximum bandwidth.

- Wi-Fi 7 access point with 2x2 MIMO tri-band Wi-Fi – parallel operation in 2.4 GHz, 5 GHz, and 6 GHz for up to 9.6 Gbps
- OFDMA for more efficient Wi-Fi channel utilization
- 1x 2.5 GE PoE+ (IEEE 802.3at) and 1x 1 GE port
- IoT support: BLE 5.4 and USB 2.0
- Housing with protection class IP50 and UL 2043
- Innovative design incl. theft-resistant and flexible mounting plate
- Power-saving functions with precise consumption monitoring
- Automated deployment, operation, and optimization via the LANCOM Management Cloud (LMC)
- WLAN controller support (including layer 3 tunneling)



LCOS LX 7.10

LANCOM LX-7200

Faster data transfer

With Wi-Fi 7, you benefit from a speed boost of up to 240% compared to Wi-Fi 6 in real-world applications. This is made possible by a doubling of the available frequency spectrum for Wi-Fi through additional 6 GHz frequencies, a doubled maximum channel width (320 MHz instead of the previous 160 MHz), and an increased data density during transmissions (4096 QAM instead of 1024 QAM in Wi-Fi 6). As a result, the LANCOM LX-7200 delivers a maximum aggregated data rate of 9.6 Gbps across all frequency bands.

More stable transmission quality

Multi-link operation (MLO) automatically uses the frequency band with better quality or even uses two frequency bands simultaneously. In addition, Multi-RU and Puncturing effectively mitigates the previously serious consequences of interference signals. This ensures significantly more reliable transmission and reception quality, especially in radio environments with high signal density.

Housing design optimized for field use

The design of the LANCOM LX-7200 is based on decades of market experience and valuable user feedback. Its flattened side contours give it a discreet appearance, allowing it to blend seamlessly into any environment. With IP50 protection rating, including rubber-sealed ports, the access point is dustproof. Additionally, it features certified fire resistance and low-smoke emissions in case of fire (UL 2043). The compact mounting bracket with a security lock not only helps prevent opportunistic theft but is also compatible with standard mounting hole patterns from various manufacturers. Optionally, the LANCOM LX-7000 series offers a specially designed mounting system for ergonomic and time-saving installation on T-bars of suspended ceilings.

Interference-free use of the 6 GHz frequency band for modern and future applications

Take a seat in the VIP lounge in the Wi-Fi: The LANCOM LX-7200 offers an exclusive Wi-Fi radio field free of interference in the 6 GHz frequency band. While the 2.4 and 5 GHz bands can be used by other wireless technologies such as alarm systems or audio applications, the broadband 6 GHz spectrum is intended for exclusive Wi-Fi use. This enables interference-free Wi-Fi connections with minimal latency and maximum data throughput. Fast-response connections and time-critical Wi-Fi applications in particular benefit from this.

Professional IoT support

With the LANCOM LX-7200, you can easily immerse yourself in the world of the Internet of Things (IoT). Support for BLE 5.4 and USB 2.0 opens up many possibilities for you to communicate with modern BLE sensors in devices or objects and to use innovative applications such as asset tracking or digital signage. In addition, the LANCOM LX-7200 is already prepared for ESL via BLE 5.4 – a future-proof solution for the long-term planning of your digital signage projects.



LCOS LX 7.10

lancom-systems.com

LANCOM LX-7200

Reduced overall energy consumption thanks to LANCOM Active Power Control

In light of rising energy costs and the growing societal demand for sustainable solutions, LANCOM Active Power Control provides the ideal answer for your network infrastructure. This intelligent, cloud-based optimization solution dynamically adjusts the available Wi-Fi capacity, reducing the energy consumption of your Wi-Fi infrastructure without compromising operational reliability. In "Sustainability Mode," the functions of the access points are minimized during idle phases, leading to a lower PoE power requirement. A centralized energy monitoring system provides full transparency of your energy consumption.



LCOS LX 7.10

LANCOM LX-7200

Wi-Fi product specification

Frequency band 2.4 GHz, 5 GHz and 6 GHz	2400-2483.5 MHz (ISM), 5150-5700 MHz (depending on country-specific restrictions), 5925-6425 MHz
Integrated Antenna Gain (peak gain)	up to 5 dBi in 2.4 GHz, up to 6 dBi in 5 GHz and up to 5 dBi in 6 GHz
Data rates IEEE 802.11be	<ul style="list-style-type: none"> → up to 5765 MBit/s according to IEEE 802.11be with MCS13/QAM-4096 at 6 GHz, 2x4 MIMO and 320 MHz channel width → up to 2882 MBit/s according to IEEE 802.11be with MCS13/QAM-4096 at 5 GHz, 2x2 MIMO and 160 MHz channel width → up to 688 MBit/s nach according to IEEE 802.11be with MCS13/QAM-4096 at 2,4 GHz, 2x2 MIMO and 40 MHz channel width
Data rates IEEE 802.11ax	<ul style="list-style-type: none"> → up to 2400 MBit/s according to IEEE 802.11ax with MCS11/QAM-1024 at 6 GHz, 2x2 MIMO and 160 MHz channel width → up to 2400 MBit/s according to IEEE 802.11ax with MCS11/QAM-1024 at 5 GHz, 2x2 MIMO and 160 MHz channel width → up to 575 MBit/s according to IEEE 802.11ax with MCS11/QAM-1024 at 2.4 GHz, 4x4 MIMO and 40 MHz channel width
Data rates IEEE 802.11n	300 Mbps according to IEEE 802.11n with MCS15 (fallback to 6.5 Mbps with MCS0).
Data rates IEEE 802.11a/ h	54 Mbps (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), fully compatible with TPC (adjustable power output) and DFS (automatic channel selection, radar detection)
Data rates IEEE 802.11b/g	54 Mbps to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection)
Output power per radio chain	<ul style="list-style-type: none"> → 2,4 GHz: 11b 13dBm; 11g 54 MBit 14dBm; HT20/40 MCS0 17/16dBm; HT40 MCS9 16dBm; HE40 MCS11 14dBm → 5 GHz: HT20 MCS0 22dBm; HT20 MCS7 20dBm; VHT80 MCS9 19dBm; HE80 MCS11 18 dBm; EHT160 MCS13 17dBm → 6 GHz: HE20 MCS0 15dBm; HE80 MCS9 18dBm; HE80 MCS11 18dBm; HE160 MCS11 18dBm; EHT320 MCS13 17dBm
Radio channels 6 GHz	Up to 24 non-overlapping channels (EU; 20 MHz channel width)
Radio channels 5 GHz	Up to 16 non-overlapping channels (available channels and further obligations such as automatic DFS dynamic channel selection depending on national regulations), configurable maximum transmit power
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (depending on country-specific restrictions), configurable maximum transmit power
Multi-SSID	Up to 16 Wi-Fi networks per radio; time-controlled activation and deactivation of Wi-Fi networks
Concurrent Wi-Fi clients	Up to 256 clients per WiFi radio
Hotspot	Support for the Cloud-managed Hotspot in combination with the LANCOM Management Cloud; Support for Frederix Hotspot (in combination with LANCOM Management Cloud)
WLAN operation modes	Access Point (infrastructure), client mode, WDS/point-to-point links



LCOS LX 7.10

LANCOM LX-7200

Supported Wi-Fi standards

IEEE standards	IEEE 802.11be, IEEE 802.11ax, IEEE 802.11ac Wave 2, IEEE 802.11n, IEEE 802.11a, IEEE 802.11g, IEEE 802.11b, IEEE 802.11i, IEEE 802.1X authenticator, IEEE 802.1X LAN supplicant (only on PoE port), IEEE 802.11h, IEEE 802.11d, IEEE 802.11v
----------------	--

Standard IEEE 802.11be

Supported features	MLO, OFDMA Multi-RUs, QAM-4096, 320 MHz channel bandwidth in 6 GHz
--------------------	--

Standard IEEE 802.11ax

Supported features	2x2 DL-/UL-MU-MIMO, DL-/UL-OFDMA, triggered target-wake-time, BSS coloring, QAM-1024, 160 MHz channels
--------------------	--

Standard IEEE 802.11ac

Supported features	2x2 MIMO, 80 MHz channels, MU-MIMO, QAM-256
--------------------	---

Standard IEEE 802.11n

Supported features	2x2 MIMO, 40-MHz channels, 20/40MHz coexistence mechanisms in the 2.4 GHz band, MAC aggregation, Block Acknowledgement, STBC (Space Time Block Coding), LDPC (Low Density Parity Check), MRC (Maximal Ratio Combining), Short Guard Interval
--------------------	--

Operating modes

Modes	Standalone, WLC-managed or LANCOM Management Cloud managed
-------	--

Wi-Fi security

Encryption options	IEEE 802.1X (WPA3-Enterprise, WPA2-Enterprise), WPA3-Personal, IEEE 802.11i (WPA2-Personal), WEP, LEPS-U (Private PSK, only possible with WPA2), LEPS-MAC
--------------------	---

Encryption algorithms	AES-CCMP, AES-GCMP, TKIP, RC4
-----------------------	-------------------------------

EAP types (authenticator)	EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, EAP-FAST
---------------------------	---

Roaming

Roaming	IAPP (Inter Access Point Protocol), Fast Roaming (802.11r), OKC, Pre-Authentication, 802.11k
---------	--

LANCOM Active Radio Control

LANCOM Active Radio Control™ 2.0	automated optimization of WLAN channels, channel bandwidth and transmit power, controlled by the LANCOM Management Cloud
----------------------------------	--

Band Steering	active steering of clients between the 2.4 GHz and 5 GHz band
---------------	---

LANCOM Active Power Control

LANCOM Active Power Control	LANCOM Sustainability Mode and energy consumption monitoring for the whole network, controlled by the LANCOM Management Cloud
-----------------------------	---



LCOS LX 7.10

LANCOM LX-7200

Bluetooth Low Energy (BLE)

Support of Bluetooth Low Energy technology (BLE) The device can scan the environment for BLE devices and can forward the resulting scan data via a REST API.

ESL communicates with BLE 5.4 compatible ESL displays (via future software update)

Layer 2 functions

VLAN 4094 VLAN IDs, static assignment to SSIDs, dynamic Assignment via LEPS-U/LEPS-MAC or 802.1X (RADIUS)

Quality of Service WME based on IEEE 802.11e

Bandwidth limitation per SSID, per Client

Multicast IGMP-Snooping, Multicast-to-Unicast-conversion on WLAN interfaces

Protocols LLDP, Proxy ARP, LACP, L2TPv3, (R)STP

Network

Protocols IPv4, IPv6, dual stack

Interfaces

Ethernet ports → ETH1: 10/100/1000/2.5 GBASE-T (RJ45/8P8C), PoE-in 802.3at
→ ETH2: 10/100/1000 GBASE-T (RJ45/8P8C)

USB 2.0 host port USB 2.0 host port (USB-A)

Internal antenna integrated Antennas for WLAN and BLE

Supported IoT Modules

IoT USB modules LANCOM Wireless ePaper USB, SES-imagotag Retail IoT Connector, Hanshow HS_C09979 ESL Controller, Hanshow HS_C09978 ESL Controller, SoluM EGU200NA0X ESL GEN2 USB Gateway

Hardware

Power consumption idle: 8.4W; max. 21.5W

Environment Temperature range 0–40 °C. Humidity 0–90 %; non-condensing

Housing robust housing made of polycarbonate and aluminium, protection class IP50, kensington-lock, 225 x 225 x 65 mm

Weight (including mounting plate) 1.82 kg

orientation sensor integrated orientation sensor (accelerometer) to detect the Access Points mounting position.

Power supply 12 V DC external plug-in power supply (not included) or PoE (Power-over-Ethernet) according to IEEE 802.3at. Operation with PoE according to 802.3af only for commissioning (no WLAN operation).



LCOS LX 7.10

LANCOM LX-7200

Management and monitoring

Management	LANCOM Management Cloud, WLAN-Controller, WEBconfig, LANconfig, LL2M, external Syslog, Packet Capturing, TACACS+
------------	--

Monitoring	LANCOM Management Cloud, WLAN-Controller, WEBconfig, LANmonitor, SNMP
------------	---

Conformity*

Europe/EFTA	CE
-------------	----

Australia / New Zealand	RCM
-------------------------	-----

Applicable for use in medical environments (EN 60601-1-2)	conforms to EN 60601-1-2
---	--------------------------

fire test	conforms to UL2043 (plenum rated)
-----------	-----------------------------------

Country of Origin	Engineered in Germany, Made in Vietnam
-------------------	--

*) Note	The full text of the specific Declaration of Conformity is available at the following Internet address: www.lancom-systems.com/doc
---------	---

Scope of delivery

Documentation	Installation Guide (DE/EN); Mounting Instructions (DE/EN)
---------------	---

Mounting	Robust low profile mounting plate, secure attachment of the device with Click-Lock
----------	--

Accessories

LANCOM PoE++ 10G Injector	1-port PoE injector with up to 10 Gigabit support, integrated power supply, compatible with the standard IEEE 802.3af/at/bt (up to 65W), item no. 61839 (EU)
---------------------------	--

LANCOM LX-7000 Universal Mount (Bulk 5)	universal mounting plate for LANCOM LX-7000 series, compatible with drill hole pattern of LANCOM LN mount and other widely used AP models, item no. 61914
---	---

LANCOM LX-7000 T-Bar Mount (Bulk 5)	Mounting kit for quick and easy mounting of LANCOM LX-7000 series APs on suspended ceilings, AL profile width 22-24 mm, item no. 61915
-------------------------------------	--

Support

Warranty extension	Free warranty extension up to 3 years (replacement service for defects) For details, visit www.lancom-systems.com/rma . The service and support conditions valid as of August 15, 2025, available at www.lancom-systems.com/pdf/LCS/ServiceSupportConditions/LANCOM-Systems-GmbH-Service-and-Support-Conditions-20250815.pdf , apply.
--------------------	---

Security updates	Up to 2 years after End of Sale of the device (but min. 3 years, see www.lancom-systems.com/product-tables), can be extended by purchasing LANcare products
------------------	---



LANCOM LX-7200

Support

Software updates	Regular free updates including new features as part of the LANCOM Lifecycle Management (www.lancom-systems.com/lifecycle)
Information on the EU Data Act	For details on product data and data on connected services, please refer to www.lancom-systems.com/eu-data-act
Manufacturer support	For LANcommunity partners up to the End of Life of the device For end customers with LANcare Direct or LANcare Premium Support during the LANcare validity
LANcare Basic S	Security updates until EOL (min. 5 years) and 5 years replacement service with shipment of the replacement device within 5 days after arrival of the defective device (8/5/5Days), item no. 10720
LANcare Advanced S	Security updates until EOL (min. 5 years) and 5 years NBD advance replacement with delivery of the replacement device within one business day (8/5/NBD), item no. 10730
LANcare Direct Advanced 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10776, 10777 or 10778)
LANcare Direct 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10752, 10753 or 10754)
LANcare Direct Advanced 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10764, 10765 or 10766)
LANcare Direct 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10740, 10741 or 10742)

Software

Lifecycle Management	After discontinuation (End of Sale), the device is subject to the LANCOM Lifecycle Management. Details can be found at: www.lancom-systems.com/lifecycle
IT Security made in Germany	The development and quality assurance take place in Germany in accordance with high security standards. The „IT Security made in Germany“ quality label of the German IT Security Association attests to the level of security achieved.

LANCOM Management Cloud

LANCOM LMC-A-1Y LMC License	LANCOM LMC-A-1Y License (1 Year), enables the management of one category A device for one year via the LANCOM Management Cloud, item no. 50100
LANCOM LMC-A-3Y LMC License	LANCOM LMC-A-3Y License (3 Years), enables the management of one category A device for three years via the LANCOM Management Cloud, item no. 50101



LCOS LX 7.10

LANCOM LX-7200

LANCOM Management Cloud

LANCOM LMC-A-5Y LMC License LANCOM LMC-A-5Y License (5 Years), enables the management of one category A device for five years via the LANCOM Management Cloud, item no. 50102


Item number(s)

LANCOM LX-7200 61927


LANCOM LX-7200 (Bulk 5) 61928

Antenna Gain


antenna pattern, 2.4 GHz




antenna pattern, 5.2 GHz



antenna pattern, 5.6 GHz



antenna pattern, 6 GHz






LCOS LX 7.10

LANCOM LX-7200

Antenna Gain

antenna pattern, BLE



LANCOM Systems GmbH
 A Rohde & Schwarz Company
 Adenauerstr. 20/B2
 52146 Wuersele | Germany
 info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity, LANCOM Service LANcare, LANCOM Active Radio Control, and AirLancer are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 05/26